# SAFETY DATA SHEET.

Issuing date 17-Nov-2015

Revision Date 17-Nov-2015

Version 1

# 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

| <u>Product identifier</u><br>Product name   | LUBE-A-ROPE (BULK)   |
|---|--|
| Recommended use of the chemical and restrictions on use   |  |
| Product code  | XF01803  |
| Synonyms  | None   |
| Supplier's details  |  |
| Recommended Use<br>Uses advised against   | Chain and Cable Lubricant.<br>No information available   |
| Manufactured For:<br>LUBEABOOM<br>P.O. Box 502366<br>Indianapolis, IN 46250<br>www.lubeaboom.com<br>PHONE: (317) 578-3961 | LUBEABOOM  |
| Emergency telephone number<br>Chemical Emergency Phone<br>Number  | 24 HR.INFOTRAC 1-800-535-5053 (US & CANADA)<br>1-352-323-3500 (INTERNATIONAL)<br>Web: infotrac.net |

# 2. HAZARDS IDENTIFICATION

## **Classification**

This SDS has been developed for sample purposes only. Flammability classification may change after Flame Ignition Testing being performed.

| Skin corrosion/irritation         | Category 2 |
|-----------------------------------|------------|
| Serious eye damage/eye irritation | Category 2 |
| Carcinogenicity                   | Category 2 |
| Aspiration toxicity               | Category 1 |
| Flammable Liquids                 | Category 2 |

# GHS Label elements, including precautionary statements

|  | Emergency Overview   |                     |
|--|--|---------------------|
| DANGER   | ~ ~  |                     |
| Hazard Statements<br>Causes skin irritation<br>Causes serious eye irritation<br>Suspected of causing cancer<br>May be fatal if swallowed and enters airwa<br>Highly flammable liquid and vapor   | ys   |                     |
| Appearance opaque  | Physical state Liquid  | <b>Odor</b> Solvent |
| Precautionary Statements - Prevention<br>Obtain special instructions before use<br>Do not handle until all safety precautions h<br>Wear protective gloves/protective clothing/<br>Wash face, hands and any exposed skin th<br>Keep away from heat/sparks/open flames/<br>Use explosion-proof electrial/ventilating/ligit<br>Keep container tightly closed<br>Ground/Bond container and receiving equit<br>Use only non-sparking tools<br>Take precautionary measures against stati | eye protection/face protection<br>horoughly after handling<br>hot surfaces. — No smoking<br>hting /equipment.<br>pment |                     |

#### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention Specific treatment (see first aid on this label) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower If skin irritation occurs: Get medical advice/attention Wash contaminated clothing before reuse IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage** Store locked up Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal** Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

None

#### Other information

0.0125% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                  | CAS-No     | Weight %* |
|--------------------------------|------------|-----------|
| NAPHTHENIC OIL, SEVERLY HYDROT | 64742-52-5 | 30-40     |
| ALIPHATIC HYDROCARBON SOLVENT  | 64742-47-8 | 30-40     |
| ACETONE                        | 67-64-1    | 10-20     |
| METHYL ACETATE                 | 79-20-9    | 1-10      |
| HYDROTREATED HEAVY NAPHTHENIC  | 64742-48-9 | 1-10      |
| PETROLEUM HYDROCARBON          | 64742-58-1 | 1-10      |
| XYLENE                         | 1330-20-7  | 0.1-1.0   |
| CARBON BLACK                   | 1333-86-4  | 0.1-1.0   |

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

## First aid measures for different exposure routes

| General advice   | Avoid contact with eyes, skin, and clothing. Avoid breathing, vapors, mist, or gas.  |  |
|--|--|--|
| Eye contact  | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek immediate medical attention/advice.  |  |
| Skin contact   | Wash off immediately with soap and plenty of water . Remove and wash contaminated clothing before re-use. Get medical attention immediately if symptoms occur.               |  |
| Inhalation   | Move to fresh air. If not breathing, give artificial respiration. If breathing has stopped, contact emergency medical services immediately.                                  |  |
| Ingestion  | Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion. |  |
| Most important symptoms/effects,   | acute and delayed  |  |
| Main Symptoms  | Causes skin and eye irritation. May cause respiratory irritaiton . Harmful if swallowed .<br>Inhalation causing Central Nervous System effects.                              |  |
| Indication of immediate medical attention and special treatment needed, if necessary |  |  |
| Notes to physician   | Treat symptomatically.   |  |
|  |  |  |

# **5. FIRE-FIGHTING MEASURES**

#### Suitable Extinguishing Media

water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

Flammable. Keep product and empty container away from heat and sources of ignition.

Explosion Data Sensitivity to Mechanical Impact none. Sensitivity to Static Discharge Yes.

#### **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

| 6. ACCIDENTAL | RELEASE MEASURES |
|---------------|------------------|
|---------------|------------------|

| Personal precautions, protective e                           | quipment and emergency procedures  |
|--|--|
| Personal precautions   | Use with adequate ventiliation to keep the exposure levels below the OELS.   |
| Environmental precautions                                    |  |
| Environmental precautions                                    | Report spills as required by local and federal regulations.  |
| Methods and materials for contain                            | ment and cleaning up   |
| Methods for Containment                                      | Prevent further leakage or spillage if safe to do so.  |
| Methods for cleaning up                                      | Contain liquid and collect with an inter, non-combustible material.  |
| 7. HANDLING AND STORAGE                                      |  |
| Precautions for safe handling                                |  |
| Advice on safe handling                                      | Avoid breathing vapors or mists. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. |
| Conditions for safe storage, including any incompatibilities |  |
| Technical measures/Storage conditions                        | Keep containers tightly closed in a dry, cool and well-ventilated place.   |
| Incompatible products  | Store away from strong acids, alkalis, or oxidizing agents.  |
| 8. EXPOSURE CONTROLS/PERSONAL PROTECTION                     |  |

#### Control parameters

| Exposure Guidelines |           |          |            |
|---------------------|-----------|----------|------------|
| Chemical Name       | ACGIH TLV | OSHA PEL | NIOSH IDLH |

#### Revision Date 17-Nov-2015

| ACETONE<br>67-64-1        | STEL: 500 ppm<br>TWA: 250 ppm               | TWA: 1000 ppm<br>TWA: 2400 mg/m <sup>3</sup><br>(vacated) TWA: 750 ppm<br>(vacated) TWA: 1800 mg/m <sup>3</sup><br>(vacated) STEL: 2400 mg/m <sup>3</sup><br>The acetone STEL does not | IDLH: 2500 ppm<br>TWA: 250 ppm<br>TWA: 590 mg/m <sup>3</sup>  |
|---------------------------|---|--|---|
|                           |   | apply to the cellulose acetate<br>fiber industry. It is in effect for all<br>other sectors<br>(vacated) STEL: 1000 ppm   |   |
| METHYL ACETATE<br>79-20-9 | STEL: 250 ppm<br>TWA: 200 ppm               | TWA: 200 ppm<br>TWA: 610 mg/m <sup>3</sup><br>(vacated) TWA: 200 ppm<br>(vacated) TWA: 610 mg/m <sup>3</sup><br>(vacated) STEL: 250 ppm<br>(vacated) STEL: 760 mg/m <sup>3</sup>       | IDLH: 3100 ppm<br>TWA: 200 ppm<br>TWA: 610 mg/m <sup>3</sup><br>STEL: 250 ppm<br>STEL: 760 mg/m <sup>3</sup>  |
| XYLENE<br>1330-20-7       | STEL: 150 ppm<br>TWA: 100 ppm               | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 435 mg/m <sup>3</sup><br>(vacated) STEL: 150 ppm<br>(vacated) STEL: 655 mg/m <sup>3</sup>       | -   |
| CARBON BLACK<br>1333-86-4 | TWA: 3 mg/m <sup>3</sup> inhalable fraction | (vacated) TWA: 3.5 mg/m <sup>3</sup>   | IDLH: 1750 mg/m <sup>3</sup><br>TWA: 3.5 mg/m <sup>3</sup><br>TWA: 0.1 mg/m <sup>3</sup> Carbon black in<br>presence of Polycyclic aromatic<br>hydrocarbons PAH |

ACGIH: (American Conference of Governmental Industrial Hygienists) OSHA: (Occupational Safety & Health Administration) NIOSH IDLH: Immediately Dangerous to Life or Health

 Other Exposure Guidelines
 Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Exposure controls

**Engineering Measures** Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

Individual protection measures, such as personal protective equipment

| Eye/Face Protection      | Safety glasses with side-shields.   |
|--------------------------|---|
| Skin and body protection | Chemical resistant apron. Protective gloves.  |
| Respiratory protection   | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. |
| Hygiene measures         | Handle in accordance with good industrial hygiene and safety practice.  |

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### **Physical and chemical properties**

Physical state Appearance Color

<u>Property</u> pH Melting/freezing point Boiling point/boiling range <u>Values</u> No information available No information available No information available

Liquid

opaque

amber

Odor Odor Threshold Solvent

Remarks • Methods

| Flash Point                        | -20 °C / -4 °F           | Based on lowest flashpoint of the products<br>constituent. |
|------------------------------------|--------------------------|--|
| Evaporation rate                   | No information available |  |
| Flammability (solid, gas)          | No information available |  |
| Flammability Limits in Air         |                          |  |
| upper flammability limit           | No information available |  |
| lower flammability limit           | No information available |  |
| Vapor pressure                     | No information available |  |
| Vapor density                      | No information available |  |
| Specific Gravity                   | 0.848                    |  |
| Water solubility                   | Practically insoluble    |  |
| Partition coefficient: n-octanol/w | vater                    |  |
| Autoignition temperature           | No information available |  |
| Decomposition temperature          |                          |  |
| Viscosity                          | No information available |  |
| Explosive properties               |                          |  |
| Other information                  |                          |  |
| VOC Content(%)                     | 0.74                     |  |
|                                    | 10. STABILITY AND        | REACTIVITY   |

#### **Reactivity**

Stable under recommended storage conditions

## **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### Conditions to Avoid

Extremes of temperature and direct sunlight.

## **Incompatible Materials**

Store away from strong acids, alkalis, or oxidizing agents.

## **Hazardous Decomposition Products**

Carbon oxides.

# **11. TOXICOLOGICAL INFORMATION**

## Information on likely routes of exposure

| Product Information | Product does not present an acute toxicity hazard based on known information                                      |
|---------------------|---|
| Inhalation          | Exposure to high vapour concentrations may cause nervous systems effects such as headache, nausea, and dizziness. |
| Eye contact         | Causes serious eye irritation.  |
| Skin contact        | Irritating to skin. Prolonged skin contact may defat the skin and produce dermatitis.                             |
| Ingestion           | Harmful if swallowed.   |

## **Component Information**

| Chemical Name                                  | LD50 Oral          | LD50 Dermal           | LC50 Inhalation     |
|--|--------------------|-----------------------|---------------------|
| ALIPHATIC HYDROCARBON<br>SOLVENT<br>64742-47-8 | > 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 5.2 mg/L (Rat)4 h |

| ACETONE<br>67-64-1                             | = 5800 mg/kg(Rat)   | -                     | = 50100 mg/m <sup>3</sup> ( Rat ) 8 h |
|--|---------------------|-----------------------|---------------------------------------|
| METHYL ACETATE<br>79-20-9                      | > 5 g/kg (Rat)      | > 5 g/kg (Rabbit)     | = 16000 ppm (Rat)4 h                  |
| HYDROTREATED HEAVY<br>NAPHTHENIC<br>64742-48-9 | > 5000 mg/kg (Rat)  | > 3160 mg/kg (Rabbit) | -                                     |
| PETROLEUM HYDROCARBON<br>64742-58-1            | > 2000 mg/kg (Rat)  | > 4480 mg/kg (Rabbit) | -                                     |
| XYLENE<br>1330-20-7                            | = 3500 mg/kg (Rat)  | > 4350 mg/kg (Rabbit) | = 29.08 mg/L (Rat) 4 h                |
| CARBON BLACK<br>1333-86-4                      | > 15400 mg/kg (Rat) | -                     | -                                     |

#### Information on toxicological effects

Symptoms

Causes skin and eye irritation. May cause respiratory irritation. Aspiration into the lungs during swallowing may cause serious lung damage.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Eye damage/irritation Sensitization Germ Cell Mutagenicity Carcinogenicity

Irritating to skin. Irritating to eyes.

There are no known mutagenic chemicals in this product.

The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

| Chemical Name             | ACGIH | IARC     | NTP | OSHA |
|---------------------------|-------|----------|-----|------|
| XYLENE                    | -     | Group 3  | -   | -    |
| 1330-20-7                 |       |          |     |      |
| CARBON BLACK<br>1333-86-4 | A3    | Group 2B | -   | -    |

ACGIH: (American Conference of Governmental Industrial Hygienists) A2 - Suspected Human Carcinogen A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans OSHA: (Occupational Safety & Health Administration)

X - Present

| A - FIESEIII                   |  |
|--------------------------------|--|
| Reproductive toxicity          | The ingredients are not reproductive hazards.                    |
| Specific target organ systemic | No information available.  |
| toxicity (single exposure)     |  |
| Specific target organ systemic | No information available.  |
| toxicity (repeated exposure)   |  |
| Chronic toxicity               | Prolonged skin contact may defat the skin and produce dermatitis |
| Target Organ Effects           | Central Nervous System (CNS), Eyes, Respiratory system, Skin.    |

May be fatal if swallowed and enters airways. Aspiration hazard

## Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0.0125% of the mixture consists of ingredient(s) of unknown toxicity The following values are calculated based on chapter 3.1 of the GHS document . 17255 mg/kg ATEmix (oral) ATEmix (dermal) 2315 mg/kg ATEmix (inhalation-dust/mist) 6.3 mg/l

## **12. ECOLOGICAL INFORMATION**

Ecotoxicity

| Chemical Name | Toxicity to algae | Toxicity to fish | Toxicity to<br>microorganisms | Toxicity to daphnia and other aquatic invertebrates |
|---------------|-------------------|------------------|-------------------------------|---|
|               |                   | •                |                               |   |

| NAPHTHENIC OIL,<br>SEVERLY HYDROT<br>64742-52-5 | -   | 5000 mg/L LC50<br>Oncorhynchus mykiss 96h   | - | 1000 mg/L EC50 Daphnia<br>magna 48h   |
|---|---|---|---|---|
| ALIPHATIC<br>HYDROCARBON SOLVENT<br>64742-47-8  | -   | 45 mg/L LC50 Pimephales<br>promelas 96h flow-through<br>2.2 mg/L LC50 Lepomis<br>macrochirus 96h static 2.4<br>mg/L LC50 Oncorhynchus<br>mykiss 96h static  | - | -   |
| ACETONE<br>67-64-1                              | -   | 4.74 - 6.33 mL/L LC50<br>Oncorhynchus mykiss 96h<br>6210 - 8120 mg/L LC50<br>Pimephales promelas 96h<br>static 8300 mg/L LC50<br>Lepomis macrochirus 96h  | - | 10294 - 17704 mg/L EC50<br>Daphnia magna 48h Static<br>12600 - 12700 mg/L EC50<br>Daphnia magna 48h |
| METHYL ACETATE<br>79-20-9                       | 120 mg/L EC50<br>Desmodesmus subspicatus<br>72h | 295 - 348 mg/L LC50<br>Pimephales promelas 96h<br>flow-through 250 - 350 mg/L<br>LC50 Brachydanio rerio 96h<br>static   | - | 1026.7 mg/L EC50 Daphnia<br>magna 48h   |
| HYDROTREATED HEAVY<br>NAPHTHENIC<br>64742-48-9  | -   | 2200 mg/L LC50<br>Pimephales promelas 96h   | - | -   |
| PETROLEUM<br>HYDROCARBON<br>64742-58-1          | -   | 79.6 mg/L LC50<br>Brachydanio rerio 96h<br>semi-static 3.2 mg/L LC50<br>Pimephales promelas 96h<br>semi-static  | - | -   |
| XYLENE<br>1330-20-7                             | -   | <ul> <li>13.4 mg/L LC50 Pimephales<br/>promelas 96h flow-through<br/>2.661 - 4.093 mg/L LC50<br/>Oncorhynchus mykiss 96h<br/>static 13.5 - 17.3 mg/L LC50<br/>Oncorhynchus mykiss 96h<br/>13.1 - 16.5 mg/L LC50<br/>Lepomis macrochirus 96h<br/>flow-through 19 mg/L LC50<br/>Lepomis macrochirus 96h<br/>7.711 - 9.591 mg/L LC50<br/>Lepomis macrochirus 96h<br/>static 780 mg/L LC50<br/>Cyprinus carpio 96h 30.26 -<br/>40.75 mg/L LC50 Poecilia<br/>reticulata 96h static 23.53 -<br/>29.97 mg/L LC50<br/>Pimephales promelas 96h<br/>static 780 mg/L LC50<br/>Cyprinus carpio 96h<br/>semi-static</li> </ul> | - | 3.82 mg/L EC50 water flea<br>48h 0.6 mg/L LC50<br>Gammarus lacustris 48h                            |

# Persistence and degradability

# **Bioaccumulation**

| Chemical Name             | log Pow     |
|---------------------------|-------------|
| ACETONE<br>67-64-1        | -0.24       |
| METHYL ACETATE<br>79-20-9 | 0.18        |
| XYLENE<br>1330-20-7       | 2.77 - 3.15 |

## Other adverse effects

No information available

# **13. DISPOSAL CONSIDERATIONS**

#### Waste treatment

Waste Disposal Methods

Contaminated packaging

Do not re-use empty containers.

# 14. TRANSPORT INFORMATION

**DOT Ground** 

UN1993, FLAMMABLE LIQUIDS, N.O.S. (ACETONE, METHYL ACETATE), 3, PGII

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261). Dispose of in accordance with federal, state, and local regulations.

# **15. REGULATORY INFORMATION**

## International Inventories

| Chemical Name                       | TSCA | DSL/NDSL | EINECS/ELI<br>NCS | ENCS       | IECSC | KECL | PICCS | AICS |
|-------------------------------------|------|----------|-------------------|------------|-------|------|-------|------|
| NAPHTHENIC OIL,<br>SEVERLY HYDROT   | Х    | Х        | Х                 | Not listed | Х     | Х    | Х     | Х    |
| ALIPHATIC<br>HYDROCARBON<br>SOLVENT | Х    | X        | Х                 | Not listed | Х     | Х    | X     | Х    |
| ACETONE                             | Х    | Х        | Х                 | Х          | Х     | Х    | Х     | Х    |
| METHYL ACETATE                      | Х    | X        | Х                 | Х          | Х     | Х    | Х     | Х    |
| HYDROTREATED<br>HEAVY NAPHTHENIC    | Х    | Х        | Х                 | Not listed | Х     | Х    | Х     | Х    |
| PETROLEUM<br>HYDROCARBON            | Х    | Х        | Х                 | Not listed | Х     | Х    | Х     | Х    |
| XYLENE                              | Х    | Х        | Х                 | Х          | Х     | Х    | Х     | Х    |
| CARBON BLACK                        | Х    | Х        | Х                 | Х          | Х     | Х    | Х     | Х    |

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

CHINA - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## U.S. Federal Regulations

#### <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| Chemical Name | CAS-No | Weight %* | SARA 313 - Threshold<br>Values % |
|---------------|--------|-----------|----------------------------------|
|               |        |           |                                  |

| XYLENE - 1330-20-7                | 1330-20-7 | 0.1-1.0 | 1.0 |
|-----------------------------------|-----------|---------|-----|
| SARA 311/312 Hazard Categories    |           |         |     |
| Acute Health Hazard               | Yes       |         |     |
| Chronic Health Hazard             | Yes       |         |     |
| Fire Hazard                       | Yes       |         |     |
| Sudden Release of Pressure Hazard | no        |         |     |
| Reactive Hazard                   | no        |         |     |

#### **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

| Chemical Name       | CWA - Reportable<br>Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous<br>Substances |
|---------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| XYLENE<br>1330-20-7 | 100 lb                         |                        |                           | Х                             |

#### <u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

| Chemical Name       | Hazardous Substances RQs | Extremely Hazardous Substances<br>RQs | RQ   |
|---------------------|--------------------------|---------------------------------------|--|
| ACETONE<br>67-64-1  | 5000 lb                  |                                       | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ |
| XYLENE<br>1330-20-7 | 100 lb                   |                                       | RQ 100 lb final RQ<br>RQ 45.4 kg final RQ  |

# U.S. State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals:

| Chemical Name            | California Prop. 65 |  |
|--------------------------|---------------------|--|
| CARBON BLACK - 1333-86-4 | Carcinogen          |  |

#### U.S. State Right-to-Know Regulations

| Chemical Name             | New Jersey | Massachusetts | Pennsylvania |
|---------------------------|------------|---------------|--------------|
| ACETONE<br>67-64-1        | Х          | X             | Х            |
| METHYL ACETATE<br>79-20-9 | Х          | Х             | Х            |
| XYLENE<br>1330-20-7       | Х          | X             | х            |
| CARBON BLACK<br>1333-86-4 | Х          | X             | Х            |

EPA Pesticide Registration Number Not applicable

# <u>Canada</u>

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

# WHMIS Hazard Class

B2 Flammable liquid D2B Toxic materials



| 16. OTHER INFORMATION |                               |                |                   |                               |  |  |
|-----------------------|-------------------------------|----------------|-------------------|-------------------------------|--|--|
| NFPA                  | Health Hazard 2               | Flammability 3 | Instability 0     | Physical and chemical hazards |  |  |
| <u>HMIS</u>           | Health Hazard 2               | Flammability 3 | Physical Hazard 0 | Personal protection B         |  |  |
| Prepared By           | Manufacturer for<br>LUBEABOOM |                |                   |                               |  |  |

Issuing date Revision Date Revision Note

**Disclaimer** 

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet